

Løfteåk 25 tonn

TECHNOMEK

Type	Rørtype	Størrelse	Maks tonnasje ved 45 grader	Standard sjakkelhull	Egenvekt i KG.
25 tonn	Firkant	2,4x2,4	25,0	38mm	73,0
25 tonn	Firkant	2,4x3,1	25,0	38mm	82,0
25 tonn	Firkant	2,4x3,6	25,0	38mm	89,0
25 tonn	Firkant	2,4x4,0	25,0	38mm	94,0
25 tonn	Firkant	2,4x5,0	25,0	38mm	107,0
25 tonn	Firkant	2,4x6,3	16,0	38mm	124,0
25 tonn	Firkant	3,1x3,1	25,0	38mm	91,0
25 tonn	Firkant	3,1x3,6	25,0	38mm	98,0
25 tonn	Firkant	3,1x4,0	25,0	38mm	103,0
25 tonn	Firkant	3,1x5,0	25,0	38mm	116,0
25 tonn	Firkant	3,1x6,3	16,0	38mm	133,0
25 tonn	Firkant	3,6x3,6	25,0	38mm	105,0
25 tonn	Firkant	3,6x4,0	25,0	38mm	110,0
25 tonn	Firkant	3,6x5,0	25,0	38mm	123,0
25 tonn	Firkant	3,6x6,3	16,0	38mm	140,0
25 tonn	Firkant	4,0x4,0	25,0	38mm	115,0
25 tonn	Firkant	4,0x5,0	25,0	38mm	128,0
25 tonn	Firkant	4,0x6,3	16,0	38mm	145,0
25 tonn	Firkant	5,0x5,0	25,0	38mm	141,0
25 tonn	Firkant	5,0x6,3	16,0	38mm	158,0
25 tonn	Firkant	6,3x6,3	16,0	38mm	175,0

Ved spørsmål vennligst ta kontakt på telefon 33 45 30 35 eller post@technomek.no